

XUNZel

applied Solar and Wind Energy





Neutral White LED Light 4000K



LED NATURE™ Series - XUNZEL

XUNZEL High-efficiency and ultra-safe 12/24V LED bulbs for solar systems.

Product Description

- Low voltage LED lighting. Ultra-safe (12/24 VDC/AC). With reverse polarity protection.
- High efficiency and very low consumption (3W, 7W or 12W depending on the model). Great luminosity and uniformity
- Neutral white light 4000K. Angle of irradiation 270°.
- Long useful life. Without maintenance.
 - They do not emit UV or near infrared radiation.
- Mercury free (0.0mg Hg).
- Instant light, no warm-up time.
- Suitable for any standard E27 base or luminaire.
- Robust, strong and elegant design.
- Connect them directly to the battery discharge controller. No need for an inverter to illuminate.
- With integrated solar driver.
- Ideal for DC applications, for example, solar, wind or hybrid off-grid (Off-Grid) and Off-Shore lighting systems: domestic or industrial lighting, street lamps, garden walkways, boat decks, harbours, driveways to garages, sheds, cabins, remote or rural areas, caravans, etc.

Model	LED NATURE 3W-12/24V	LED NATURE 7W-12/24V	LED NATURE 12W-12/24V
XUNZEL Code	XLED03124K	XLED07124K	XLED12124K
Consumtion	3W	7W	12W
Incandescent Equivalent	25W	60W	75W
Nominal Voltage	12/24VDC /AC	12/24VDC /AC	12/24VDC /AC
Current Consumption 12/24VDC	381mA @ 12V 216mA @ 24V	570mA @ 12V 290mA @ 24V	1060mA @ 12V 480mA @ 24V
Luminous Flux (lumens)	270lm	630lm	1080lm
Luminous Efficiency	>90lm/W		
Ilumination Angle	270°		
Temperature	4000K - Neutral white light		
Color Rendering Index (CRI)	80		
Ambient Temperature / Humidity	-20°C ~ 50°C / Max. 95%		
Protection Grade	IP40		
Bushing Type	E27		
Diameter / Length	55/97mm 70/135mm		
Lifetime	25.000h (B50L70) = 25 years (2.7h/day)		

XU-2210112-PL | XUNZEL™ reserves the right to make changes and improvements without prior notice



© XUNZEL ENERGY SL www xunzel com



























